

Practicus drain body DN 70, Vertical outlet



Article information

Item no.: 45270
GTIN: 4026092033586
Price group: 10

Advantages

- Hygiene: hygienic, absolutely corrosion-free and durable material
- absolutely corrosion-free and durable material
- Fire protection: combinable with the Fire-Kit for fire and smoke protection

Description

In combination with an upper section, the Practicus polymer drain body is used for point drainage and is equipped with a removable odour trap and a temporary protective cover. The drain meets particular sound insulation requirements in accordance with the measurements of the Fraunhofer Institute in Stuttgart.

| | |
|---|---------------------------|
| Variant | |
| System: | 125 |
| Waterproofing layer on the upper section: | Connection flange |
| Waterproofing layer on the drain body: | Connection flange |
| Sealing water height: | 50 mm |
| General characteristics | |
| Nominal size (DN): | 70 |
| Outer diameter (OD): | 75 mm |
| Inlet max. scoring (DN): | Z-19.53-2414,Z-19.17-1719 |
| Dimensions | |
| Net weight: | 0,6 kg |
| Gross weight: | 0,71 kg |
| Diameter: | 135 mm |
| Height: | 201 mm |
| Packaging dimension: | length |
| Packaging dimension: | width |
| Packaging dimension: | height |
| Tank/drain body | |
| Number of outlets: | 1 |
| Material of drain body: | PP |
| System: | vertical |

Coverage features

Odour trap:

included