


## Practicus floor/roof drain DN 100, horiz, Waterpr layer, Des grate





## **Article information**

Item no.: 45110.53 GTIN: 4026092052815

Price group: 10

## **Advantages**

- Hygiene: hygienic, absolutely corrosion-free and durable material
- Sound insulation: outstanding sound insulation effect confirmed by the Fraunhofer Institute

## **Description**

The Practicus floor drain is used for point drainage and is equipped with a connection flange as well as a removable odour trap, a lip seal and a temporary protective cover. Including telescopic height-adjustable upper section made of ABS. The drain meets particular sound insulation requirements in accordance with the measurements of the Fraunhofer Institute in Stuttgart. The outlet socket is suitable for connection to SML cast iron pipes. With connection option for equipotential bonding.

Variant

System: 125

Waterproofing layer on the upper section: Enclosed sealing collar to be glued (bd) according to

DIN 18534

Waterproofing layer on the drain body: Connection flange

Sealing water height: 50 mm Discharge rate (l/s) with 20 mm backwater: 1,6

General characteristics

Standard:EN 1253-1Nominal size (DN):100Outer diameter (OD):110 mm

**Dimensions** 

Vertical adjustment: 10 - 23 mm Net weight: 2,62 kg



Gross weight: 3,38 kg

Vertical adjustment: vertically adjustable upper section

Packaging dimension: length
Packaging dimension: width
Packaging dimension: height

Tank/drain body

Number of outlets: 1

Connection inlet/outlet sockets: The outlet spigot is suitable for connection to SML

pipes.

Material of drain body: PP System: lateral

Coverage features

Type of cover: Design cover

Cover material: Stainless steel 14301

Colour of cover:silverWidth of cover:120 mmLength of cover:120 mmSurface:ground

Frame material: Stainless steel 14301

Cover locking: Lock & Lift Load class: L 15 (EN 1253-1)

Grating colour: Kessel

Slip resistance class: R9 according to DIN 51130; C according to DIN

51097

Rim length: 132 mm Rim material: 132 mm

Upper section: adjustable in three dimensions

Shape of upper section: square
Upper section material: ABS
Odour trap: included